

TECHNICAL DATA

Fluke 80PK-8 Pipe Clamp Temperature Probe



Key features

- Durable ribbon sensor
- Measurement range: -29 to 149 °C for pipe diameters from 6.4 to 34.9 mm
- One year warranty

Product overview: Fluke 80PK-8 Pipe Clamp Temperature Probe

The Fluke 80PK-8 Pipe Clamp Temperature Probe uses Type-K thermocouple for fast temperature and superheat measurements of pipe surfaces. The 80PK-8 Type K Thermocouple Pipe Clamp Temperature Probe is designed to reliably measure the temperature of pipes $\frac{1}{2}$ -inch (6 mm) to 1 3/8-inch (35 mm) in diameter, at temperatures between -29 °C and 149 °C (-20 °F and 300 °F), while retaining a long service life.



Ordering information



80PK-8

Fluke 80PK-8 Pipe Clamp Temperature Probe

Pipe Clamp Temperature Probe





Preventive maintenance simplified. Rework eliminated.

Save time and improve the reliability of your maintenance data by wirelessly syncing measurements using the Fluke Connect $^{\mathtt{m}}$ system.

- Eliminate data-entry errors by saving measurements directly from the tool and associating them with the work order, report or asset record.
- Maximize uptime and make confident maintenance decisions with data you can trust and trace.
- Access baseline, historical and current measurements by asset.
- Move away from clipboards, notebooks and multiple spreadsheets with a wireless one-step measurement transfer
- Share your measurement data using ShareLive™ video calls and emails.

Find out more at flukeconnect.com







All trademarks are the property of their respective owners. WiFi or cellular service required to share data. Smartphone, wireless service and data plan not included with purchase. First 5 GB of storage is free. Phone support details can be viewed at fluke.com/phones.

Smart phone wireless service and data plan not included with purchase. Fluke Connect is not available in all countries.

Fluke. Keeping your world up and running.®

Fluke Europe B.V.
P.O. Box 1186
5602 BD Eindhoven
The Netherlands
www.fluke.com/en
©2024 Fluke Corporation. All rights reserved.
Data subject to alteration without notice.
07/2024

Modification of this document is not permitted without written permission from Fluke Corporation.

For more information call: In Middle East/Africa +31 (0)40 267 5100