

DIGITAL MILLIOHM METER



Features

- 11000-count LCD
- Easy to carry and easy to use
- Compact and lightweight
- Four terminal measurement for milliohm
- Measuring ranges :
1100.0 mΩ in steps of 100 μΩ
11000 mΩ in steps of 1 mΩ
- Measures down to 100 μΩ (0.1 mΩ)
- Large LCD indication (74 x 45 mm viewing area)
- Testing current :
1100.0 mΩ : 100 mA approx.
11000 mΩ : 10 mA approx.
- Data hold function
- Power source : 1.5V AA Alkaline battery x 6
- Low battery indication
- Protection fuse : 200mA / 250V x 1
- Operation temperature : 0 ~ 40°C
- Relative humidity : 80% max



mΩ measurement (4-wire method)

Measuring ranges (mΩ)	0~1100.0mΩ in steps of 100μΩ 0~11000mΩ in steps of 1mΩ
Accuracy	±0.8% of reading ±4 digits over the operating temperature range 0°C ~ 40°C, with the supplied test leads
Protection fuse	200mA/250V × 1
Dimensions	207(L) × 188(W) × 68(D) mm
Weight (battery included)	Approx. 950g
Power source	1.5V "AA" Alkaline battery × 6
Safety standard	IEC/EN 61010-1 IEC/EN 61326-1
Accessories	Instruction manual Test leads Shoulder belt Batteries



AL-4136C C

BET-1652